



PLASMA CUTTING SYSTEM

CUTMASTER 12 PLUS (SL60)

1ph, 50/60Hz, 110 / 230V Input / 40A Output.
 12 mm Genuine Cut Capacity
 Efficiency - 230V = 13.5A 110V = 16.3A



System Specifications

Cut Capacity	Input	Output	Duty Cycle	Dimensions (HxWxD)	Weight
Genuine Cut: 12 mm (230V) Genuine Cut: 8 mm (110V)	1ph, 110 / 230V, 50/60Hz	40A (230V) 27A (110V)	40% @ 40A (230V) 30% @ 27A (110V)	228 x 117 x 470 mm	11.8kg

Part No.	Description	List Price £
1-4200-4SL60	Cutmaster 12 Plus Includes Power Supply, SL60™ Torch with 6.1m leads, Mains Cable, Work Cable & Clamp, Spare Parts, Carry Bag, Gloves, Cutting Glasses.	1,715 .00

REPLACEMENT TORCH AND PARTS

		Pack Qty	
7-5204	SL60, (75°) Hand Torch and Lead package, 6.1m with ATC Connector	1	451.21
9-8219	75° Torch Head	1	262.82
9-8207	Drag Tip - 40A	5	5.03
9-8208	Standard Cutting Tip - 40A	5	5.03
9-8215	Electrode	5	7.35
9-8213	Start Cartridge	1	21.00
9-8218	Standard Shield Cup	1	18.88

For the full range of 1Torch consumables and torches, please refer to pages 16 - 19

OPTIONS AND ACCESSORIES

7-7507	Air Filter Kit	100.87
9-7741	Replacement Filter Cartridge	28.73
7-7501	Basic Cutting Guide Kit	86.36
7-8910	Cutting Guide Kit Deluxe	213.15
7-8888	Multi-Purpose Cart	217.13
7-8911	Straight Line Cutting Guide	225.36
9-1260	Leather Lead Cover 6.1m	90.17
9-1280	Leather Lead Cover 15.2m	180.30

Features

- Automatic voltage selection to 110V / 230V input power
- Lighter weight design for maximum portability
- SL60 torch is more robust for enhanced durability
- 3 Year Warranty Machine / 1 Year Warranty Torch
- Surelok® electrode eliminates tip wobble found in some blow-apart torch designs, resulting in a cleaner arc and longer parts life
- Precision-engineered consumable parts are easy to change and require no tools
- Easy-to-use torch trigger release and ergonomic handle provide comfort during long cutting sessions