Lincoln Electric Europe



TAKE THE ADVANTAGE

The Vantage® 400 CE and 500 CE are ones of the most compact and powerful engine-driven welders / generators in the construction, pipe or rental fleet market today.

They are also the most quiet, with a smooth running 4-cylinder Perkins® water-cooled diesel engines.

Use these multi-process welders for Stick welding with a large variety of electrodes, Lift TIG welding, CV welding with shielding gas or Innershield wires, and arc gouge up to 8 mm carbons for Vantage 400 and 10 mm carbons for Vantage 500.

You will value the superior arc performance delivered by exclusive Lincoln Chopper Technology $^{\text{TM}}$.

You will also appreciate VRD™ (Voltage Reduction Device™), which reduces OCV (open circuit voltage) in the CC-Stick weld mode for added safety. These models effectively generate high auxiliary power on 3-phase or 1-phase AC to power your lights, grinders, power tools, Inverters, etc...

Last but not least, they are housed in a rugged, low maintenance stainless steel enclosure and loaded with many innovative service features.

CHOPPER TECHNOLOGY™

Traditional technology



The weld control is more variable around the desired output.

Chopper technology™



Extremely fast response for tighter output control.

Patented and award-winning Lincoln Chopper Technology™ delivers superior DC arc welding performance for general purpose stick, Downhill Pipe, DC TIG, MIG, cored-wire and arc gouging. Benefits of Chopper Technology include:

- Easy arc starting
- Smooth arc action
- Low spatter levels
- Excellent bead Appearance

ADVANTAGE

Compact, multi-process, excellent value

- ✓ Compact case

 with stainless steel enclosure
- ✓ Arc gouging
 up to 8mm (V400) & 10mm(V500)
- ✓ Downhill pipe welding mode

Excellent for cellulosic electrodes

- ✓ Built-in "hot start"

 for easier starts and restrikes
- ✓ Reliable engine 4 cylinder

water cooled,1500rpmPerkins Diesel engine

✓ Innovative Service Access

with auto-reconnect between 115/230V

- ✓ VRDTM device for added safety
- ✓ Low noise to fit with new European norms
- ▼ Built the Lincoln Way

 Robust and reliable
- ✓ 3 Years Full Parts and Labour Warranty



TECHNICAL SPECIFICATIONS

Product	Item Number	Rated output	Ouput range	AC generator power	AC generator receptacles	Weight	Dimensions HxWxD (mm)
Vantage 400	K2502-3	350A / 34V @ 100% 400A / 30V @ 60%	30-400A	13.2 kW	115V / 1ph	560 kg	913 x 642 x 1524
Vantage 500	K2503-3	400A / 36V @ 100% 450A / 38V @ 60%	30-500A	14.5 kW	220V / 1ph 400V / 3ph	586 kg	913 x 687 x 1590

ENGINE SPECIFICATIONS

Product	Model	Description	Horse power & displacement	Operation speeds (rpm)	Fuel Consumption (I/hr)	Noise	Capacities (I)
Vantage 400	Perkins 404D-22	4 cylinders 4 cycles Water cooled 12V electric start	28HP@ 1500rpm 2200cm ³	Full load : 1500 Low idle : 1200	4.81 1.10	Sound power : 96Lwa* - Sound level : 71dBA @7m	Fuel : 76 Oil : 10.6 Coolant : 7.6
Vantage 500	Perkins 404D-22 turbo	Dry type air cleaner Fuel with water sepa- rator (Turbo for V500)	38HP@ 1500rpm 2200cm ³	Low rate . 1200	6.50 1.16		

ACCESSORIES

Item Number	Description		
KIT400A-70-5M	Cable kit 400A, 70mm², 5m		
GRD-400A-70-5M	Ground cable kit 400A, 70mm², 5m		
K10095-1-15M	Control box, 1 potentiometer, 6 pins, 15m		
K10398	Extension cable for remote control box, 15m		
K10419-1-INST	TIG box +V270T, installed		
K903-1	Spark arrestor		
K10417-I-INST	Petrochemical kit factory installed		
K2641-2	4-wheel steerable trailer (offroad, plant, yard)		
K2636-1	2-wheel undercarriage		
K10418-1-INST	Road undercarriage, factory installed		



- Glow Plug Button
- Weld Mode Selector Switch
- 3. Run/Stop Switch
- Hour Meter
- 5. Start Push Button
- 6. Engine Idler Switch
- 7. Fuel Level, Engine Temperature, Oil Pressure Gauges
- 8. Engine Protection Light
- 9. Engine Battery Charging Light
- 10. 14-Pin Wire Feeder Connector
- 11. 6-Pin Remote Control Connector
- 12. Arc Force & Inductance/Pinch Ctrl Dial
- 13. Welding Terminals Control Switch
- Wire Feeder Voltmeter Polarity Switch
- Digital Amps and Volts Output Meters
- 16. VRD Indicator Lights
- 17. Output Control Dial



United Kingdom : Lincoln Electric (UK) Ltd. Tel: +44 114 287 2401 Fax: +44 114 287 2582

France: Lincoln Electric France SAS Tel: +33 232 11 40 40 Fax: +33 232 11 40 11

Germany: Lincoln Electric Deutschland Tel: +49 2102/7 13 96-0 Fax: +49 2102/ 7 13 96-31

Italy: Lincoln Electric Italia, SRL Tel: +39 010 754 111 Fax: +39 010 754 1150

The Netherlands: Lincoln Smitweld B.V.
Tel: +31 24 352 29 11 Fax: +31 24 352 22 02

Denmark: Lincoln Electric Nordic Tel: +45 86 26 51 00 Fax: +45 86 26 51 50

Spain: Lincoln KD, Sa Tel: +34 93 685 9600 Fax: +34 93 685 9610

Poland: Lincoln Electric Bester S.A.
Tel: +48 746 46 1100 Fax: +48 746 46 1082

Other countries: Lincoln Electric Europe B.V. Tel: +31 24 352 29 27 Fax: +31 24 352 29 29

