



ProtectoAutoclenz 415v

Portable fume extractor



ProtectoAutoclenz is a self cleaning mobile fume filter type PF incorporating a separator, a durable large surface area filter cartridge, complete with a filter monitor, post-cleaning function and hour meter. The unit is capable of handling up to 3000 m³/hr and is available with a 2, 3 or 4metre 150mm diameter hose type arm with internal support structure.

The unit has a 1.5 kW fanset and is supplied with a 5m mains input cable. ProtectoAutoclenz weighs 160kg and is supplied on swivel castors for manoeuvrability.



Features

- Cleaner Work Environment: Reduces fumes and particulate in the operator and surrounding work areas.
- Long lasting, durable filter cartridge
- Low Noise Level
- Operating hours meter
- Optical and acoustic filter monitoring
- 5m mains cable

Ordering information

ProtectoAutoclenz Mobile Extractor 2m 3ph 415v	EXT3AUT2415
ProtectoAutoclenz Mobile Extractor 3m 3ph 415v	EXT3AUT3415
ProtectoAutoclenz Mobile Extractor 4m 3ph 415v	EXT3AUT4415
Pre-coat for filter cartridges, 100g	EXT9510050001
Filter Cartridge 10m2 BIA M 327 x 600mm	EXT10025
Optional Spark Latch 160mm	EXT95014901601
2m Replacement Hose	EXT101925
3m Replacement Hose	EXT101926
4m Replacement Hose	EXT101927



ProtectoAutoclenz Twin 415v

Portable fume extractor



ProtectoAutoclenz Twin is a self cleaning mobile fume filter type PF incorporating a separator, a durable large surface area filter cartridge, complete with a filter monitor, post-cleaning function and hour meter. The unit is capable of handling up to 3500 m³/hr and is complete with 2x 2, 3 or 4metre 150mm diameter hose type arm with internal support structure.

The unit has a 2.2 kW fan set and is supplied with a 5m mains input cable. ProtectoAutoclenzTwin weighs 190kg and is supplied on swivel castors for manoeuvrability.



Features

- Cleaner Work Environment: Reduces fumes and particulate in the operator and surrounding work areas.
- Two long lasting, durable filter cartridge.
- Optical and acoustic filter monitoring
- Operating hours meter
- 5m mains cable

Ordering information

ProtectoAutoclenz Twin Mobile 2m 415v	EXT3AUT2415T
ProtectoAutoclenz Twin Mobile 3m 415v	EXT3AUT3415T
ProtectoAutoclenz Twin Mobile 4m 415v	EXT3AUT4415T
Filter Cartridge 10m2 BIA M 327 x 600mm	EXT10025
Pre-coat for filter cartridges, 100g	EXT9510050001
Optional Spark Latch 160mm	EXT95014901601