

BODE MEDIUM DUTY COLUMN PRECISION AND PERFORMANCE



Model 3/TRMB 4 m x 5 m
Tracked unit with rotating column.

Model 3/TRMB 5 m x 4 m
Set-up for seamless pipe
welding using submerged arc
welding unit.



Model 3/TRMB
Utilised as shown in stainless
steel container welding role.
Container carried on Bode
SA2100 Rotators.
Remote control master station.

& BOOM MANIPULATORS FROM EVERY ANGLE

Model	Min. Height under Boom (mm)	Max. Height under Boom (mm)	Overall Height (mm)	Boom reach (mm)	Boom Travel speed (mm/min.)	Max. Load (kg)
2/RMB 2x2	550	2000	2400	2000	100-2000	140
2/RMB 2x2.5	550	2000	2400	2500	100-2000	120
2/RMB 2.5x2	550	2500	2900	2000	100-2000	140
2/RMB 2.5x2.5	550	2500	2900	2500	100-2000	120
2/RMB(HD) 2x2	575	2000	2500	2000	100-2000	215
2/RMB(HD) 2x2.5	575	2000	2500	2500	100-2000	190
2/RMB(HD) 2.5x2	575	2500	3000	2000	100-2000	215
2/RMB(HD) 2.5x2.5	575	2500	3000	2500	100-2000	190
2/RMB(HD) 3x2	575	3000	3500	2000	100-2000	215
2/RMB(HD) 3x2.5	575	3000	3500	2500	100-2000	190
2/RMB(HD) 3x3	575	3000	3500	3000	100-2000	170
2/RMB(HD) 3x3.5	575	3000	3500	3500	100-2000	150
2/RMB(HD) 3x4	575	3000	3500	4000	100-2000	125
2/RMB(HD) 3.5x2	575	3500	4000	2000	100-2000	215
2/RMB(HD) 3.5x2.5	575	3500	4000	2500	100-2000	190
2/RMB(HD) 3.5x3	575	3500	4000	3000	100-2000	170
2/RMB(HD) 3.5x3.5	575	3500	4000	3500	100-2000	150
2/RMB(HD) 3.5x4	575	3500	4000	4000	100-2000	125
2/RMB(HD) 4x2	575	4000	4500	2000	100-2000	215
2/RMB(HD) 4x2.5	575	4000	4500	2500	100-2000	190
2/RMB(HD) 4x3	575	4000	4500	3000	100-2000	170
2/RMB(HD) 4x3.5	575	4000	4500	3500	100-2000	150
2/RMB(HD) 4x4	575	4000	4500	4000	100-2000	125
3/RMB 3x2.5	680	3000	4190	2500	100-2000	430
3/RMB 3x4	680	3000	4190	3000	100-2000	370
3/RMB 3x3.5	680	3000	4190	3500	100-2000	310
3/RMB 3x4	680	3000	4190	4000	100-2000	250
3/RMB 3.5x2.5	680	3500	4690	2500	100-2000	430
3/RMB 3.5x3	680	3500	4690	3000	100-2000	370
3/RMB 3.5x3.5	680	3500	4690	3500	100-2000	310
3/RMB 3.5x4	680	3500	4690	4000	100-2000	250
3/RMB 4x2.5	680	4000	5190	2500	100-2000	430
3/RMB 4x3	680	4000	5190	3000	100-2000	370
3/RMB 4x3.5	680	4000	5190	3500	100-2000	310
3/RMB 4x4	680	4000	5190	4000	100-2000	250
3/RMB 4.5x2.5	680	4500	5690	2500	100-2000	430
3/RMB 4.5x3	680	4500	5690	3000	100-2000	370
3/RMB 4.5x3.5	680	4500	5690	3500	100-2000	310
3/RMB 4.5x4	680	4500	5690	4000	100-2000	250
3/RMB 4.5x4.5	680	4500	5690	4500	100-2000	190
3/RMB 5x2.5	680	5000	6190	2500	100-2000	430
3/RMB 5x3	680	5000	6190	3000	100-2000	370
3/RMB 5x3.5	680	5000	6190	3500	100-2000	310
3/RMB 5x4	680	5000	6190	4000	100-2000	250
3/RMB 5x4.5	680	5000	6190	4500	100-2000	230
3/RMB 5x5	680	5000	6190	5000	100-2000	200



YOU'LL NOTICE THE DIFFERENCE WITH BODE

BODE
Positioners

BODE
Service

BODE
Hire

Globally the Bode range of Column & Boom Manipulators stands out not only for innovation in design and quality of manufacture, but also for reliability and robustness.

- 360° powered column rotation with manual locking at any position.



- Free standing or variable speed travelling carriage.
- Optional fittings, including welding heads, available.



Whatever your need Bode will have the answer. Just talk to us, and remember, Bode also makes other ranges of Column & Boom Manipulators from portable to ultra heavy duty models.

- Variable speed boom.
- Boom elevation through geared motor rack and pinion drive with elektro-magnetic brake.
- Elevation and traverse drive mounted on saddle providing for easy access servicing and maintenance.
- Machines fully counter-balanced by column internal weight, connected to the saddle by heavy duty wire rope. Anti-fall device offers full safety feature.
- Extra wide rollers and unique slideways ensure minimum deflection traversing.
- Innovative machined 'V' ways to column ensure that the boom saddle moves smoothly with no vibration. This reduces wear and tear.



F. Bode & Sons Limited

Unit No.1, Stubbins Lane
Claughton-on-Brock
GB-Preston, Lancs PR3 0QH

Tel.: +44 (0) 1995 643 210
Fax: +44 (0) 1995 643 211
E-mail - sales@bode.co.uk

Visit our web site - www.bode.co.uk