

ORBITAL WELDING POWER SOURCE SAXX-201





NEW!

SAXX-201



Main features

Latest generation, easy-to-use power supply with simple, intuitive programmation and full data acquisition including welding head and internal interting gas flows.

Handle and strap for easy transport

Screen protection

Intuitive and simple programmation

Automatic parameters calculation and programming assistance

7" color touch screen Multilingual menu 3 login levels (operator, welder and administrator)

Two independent gas lines with flow management (optional)

Welding torch gas control, and optional internal inerting gas flow control

Wire feeder connector



Wifi (optional)

Remote control via smartphone or tablet

Send and retrieve data

Integrated printer

Printing programs and actual parameters

Data acquisition on USB key

Saves up welding programs and users profiles

The system monitors and saves welding parameters each second

Data can be viewed directly on the screen or via the supplied "WeldData" software, which can be converted to DMOS/ QMQS format.

(optional)

to synchronize the wire feed with the current pulse

Removable water cooling sytem

Cooling capacity 700W, flow mini alarm

Can be separated without tools and makes the power supply extremely portable



Compatible with all AXXAIR closed heads

and most closed heads on the market (AMI, Polysoude, ESAB, Orbitec, Orbitalum, and MK product)



SAXX-201




Technical characteristics

Description	Orbital TIG welding power supply, 200A, autoline					
Welding current type	DC					
Supply voltage	Single phase main with earth 110 to 230 V+/- 15% 50/60Hz					
Duty cycle	200A / 25% at 230V 140A / 35% at 110 V 115A / 100% at 230V 100A / 100% at 110V					
IP standard	IP21					
Data acquisition	USB key					
Alarms	Arc voltage sensors, gas flow sensors, cooling liquid sensors, inverter operation alarm, motorizations alarm (machine and wire feeder)					
Screen size	7"					
Languages	French, English, German, Spanish, Italian, Russian, Chinese, Korean, Japanese, Turkish, Dutch, Polish, Portuguese, Slovak and Hungarian					
Industry 4.0 connections	Ethernet port / Wifi (optional)					



You can configure your SAXX-201 power supply with the options you need:

	Cooled	Gas line	Options				
Product code			Second gas line	Wire feed	Wifi	Net weight	Dimensions AxBxC
SAXX-201	AIR	•				21 kg	
SAXX-201I	AIR	•			•	21 kg	
SAXX-201W	AIR	•		•		21 kg	468 mm
SAXX-201DG	AIR	•	•			21 kg	X 0.40,
SAXX-201IW	AIR	•		•	•	21 kg	249 mm x
SAXX-201DGI	AIR	•	•		•	21 kg	482 mm
SAXX-201DGW	AIR	•	•	•		21 kg	
SAXX-201DGIW	AIR	•	•	•	•	21 kg	
SCOOL-700	Water cooler (700W)		al to the use nes. Compa models lis	8 kg	468 mm x 249 mm x 146 mm		





Accessories available (see compete catalog)

- Wired remote control*
- Trolley
- · Gas splitter pipe
- Switchbox

- TIG manual torch
- Wire feeder
- Adapter kit for connecting competitors heads
- * Remote control available as an accessory, only compatible with the SAXX-201 with Wifi option

Westermans International Ltd Unit 4 Midland Distribution Centre Markfield Road, Groby Leicestershire, LE6 0FS