

CONTROL UNIT FCU-20



/ The FCU-20 is a compact control unit for turntables (FTT 10/40/150, FRT 50/150H), specially for circumferential welding operations (MIG/MAG, TIG and Plasma).

STANDARD EQUIPMENT


- / Touchscreen display with graphical user interface
- / Exchangeable protective film (spatter resistant)
- / Alternative operation via multifunctional rotary button
- / Parameter input while the running program sequence
- / PLC control with frequency inverter
- / EMC compatible
- / HF-compliant
- / 2-step mode
- / Control line for turntable 3,5 m (138 in)
- / Control line for power source 5 m (198 in)
- / Mains cable with plug 5 m (198 in)

ACCESSORIES

- / Rob 3000 interface for Job-mode
- / I-kit Job-mode for 2nd power source
- / I-kit Activation FRC 1
- / I-kit Activation FRT 150
- / I-kit Welding step axis
- / Connection cable 5 m (197 in) to FCU-11/FCU-12
- / Connection cable 3 m (118 in) to KD 4010
- / Connection cable 5 m (197 in) to FPT
- / Uptake FCU



/ Touchscreen



/ Multifunctional rotary button



/ Exchangeable protective film

FUNCTIONS

- / Main switch on/off
- / Start/stop
- / Welding on/off
- / Welding direction
- / Fine positioning
- / Rapid motion
- / Pneumatic on/off
- / External device Start/stop
- / Successor programs
- / Monitoring current-flow signal
- / Emergency stop


PARAMETER

- / Start-up time lag
- / Job-selection (Rob 3000 necessary)
- / Overlap time
- / Downslope time
- / Endcrater-current time
- / Time lag for external start
- / Cooling time
- / Flying start
- / Welding direction
- / Rotation speed
- / Pneumatic on/off
- / Successor programs on/off
- / Reversing on/off
- / External start

TECHNICAL DATA

FCU-20	
Mains voltage, 50 - 60 Hz	230 V
Control voltage	24 V
Mains fuse	1,5 A
Power consumption	230 VA
Dimensions l/w/h	350 x 245 x 160 mm (13.8 x 9.7 x 6.3 in)
Weight	6,1 kg (13.4 lb)

SYSTEM OVERVIEW



/ Battery Charging Systems / Welding Technology / Solar Electronics

WE HAVE THREE DIVISIONS AND ONE PASSION: SHIFTING THE LIMITS.

/ Whether Battery Charging Systems, Welding Technology or Solar Electronics - our goal is clearly defined: to be the technology and quality leader. With more than 3,000 employees worldwide, we shift the limits of what's possible - our 737 active patents are testimony to this. While others progress step by step, we innovate in leaps and bounds. Further information about all Fronius products and our global sales partners and representatives can be found at www.fronius.com.

Axson Teknik är certifierade enl. ISO 9001:2008





Medlem i

