

BENCH POSITIONERS



Machine illustrated, fitted with self-centering gripper chuck – optional extra.

1.VH BENCH POSITIONER

- Capacity – 50 kg at 75 mm ecc. and 150 mm c.o.g. – table vertical
- Table diameter 460 mm, fully machined with concentric rings and slots to enable workpiece to be readily secured.
- Manual tilting through 360°
- Variable speed table rotation 0,3 – 6,0 r.p.m.
- Built in earthing 150 amps.
- Forward/stop/reverse controls.
- Supply voltage: 220 V / 240 V., 1 Ph, 50 Hz

Optimal Extras;

- Stop/start footswitch with 3 m cable.
- Support stand.
- Can be supplied having 75 mm. diameter hole through the centre of table and spindle



1.HV BENCH POSITIONER

- Capacity – 25 kg at 75 mm ecc. and 75 mm c.o.g. – table vertical
- Table diameter 300 mm, fully machined with concentric rings and slots to enable workpiece to be readily secured.
- Manual table tilting through 360°
- Variable speed table rotation through 360°
- Speeds: 0,3 – 3,0 r.p.m. or 0,6 – 6,0 / 1,1 – 12,0 r.p.m
- Built in earthing 150 amps.
- Forward/stop/reverse controls.
- Supply voltage: 220 V / 240 V., 1 Ph, 50 Hz

**ON TRACK TO TURN OUT
A PERFECTLY ENGINEERED PRODUCT**



F. Bode & Sons Limited

Unit No 1 Stubbins Lane
Claughton-On-Brock
Preston, Lancs
England
PR3 0QH

Tel.: +44 (0) 1995 643 210
Fax: +44 (0) 1995 643 211
E-mail - sales@bode.co.uk

Visit our web site -
www.bode.co.uk