MODEL 415

PROGRAMMABLE MULTI-FUNCTION WELD POWER SUPPLY



State-of-the-Art Technology with Unparalleled Flexibility and Capability





M415 Program Execution Screen

The Model 415 is an all-in-one computer controlled GTAW power supply. It is primarily designed to work with AMI's orbital and fixed automation weld heads. The Model 415 power supply can control third party positioners and welding manipulators.





The Model 415 incorporates a powerful automation controller designed to meet the challenges of the most demanding welding applications. At the heart of the power supply is an industrial computer programmed via a large 12" touch screen or keyboard. The intuitive graphical user interface (GUI) makes programming easy using standard welding industry terminology and clearly organized input fields.

UICK SPECS

Input Power

200 - 575 VAC Service, 3-phase 50/60 Hz

Weld Current

5 - 400 A 100% Duty Cycle

I/O Devices

2 USB ports RS232 serial interface Data acquisition output Ethernet over fiber optic

Memory Capacity

Over 1000 weld programs

Water Cooler

Included 710 lbs. (325 kg)

Dimensions

39" x 26" x 36" (990 mm x 660 mm x 915 mm)

Weight













MODEL 415 PROGRAMMABLE MULTI-FUNCTION WELD POWER SUPPLY

STANDARD HARDWARE




The Model 415 power supply has many standard hardware and software features. The power supply contains all the hardware and control elements of a welding automation cell in a highly integrated compact package. It can easily be switched between orbital and fixed automation applications.



- Computer controlled, solid state, pulsed, and air cooled GTAW inverter
- 12" touch screen graphical user interface (GUI) to display all weld data
- High capacity, programmable memory for storage of weld schedule information
- Current servo plus 4 Standard Closed Loop velocity servos
- 2 programmable auxiliary outputs for Hot Wire and travel control
- Integrated water cooler for welding torch and weld head cooling
- 2 USB and 1 Ethernet ports
- Full function remote pendant
- · HF or Lift Start arc initiation
- Data streaming output via RS232
- Parallel printer connector
- Compact size keyboard

OPTIONAL HARDWARE





Data Acquisition Module

- 4 closed loop motor servos
- 8 open loop motor drives for positioning and job functions
- High resolution, digital remote vision systems
- Auxiliary water cooler for cameras
- Digital data acquisition module or chart recorder
- Remote control PC interface via Ethernet LAN

PROGRAMMABLE FUNCTIONS





Welding Current Control



Arc Voltage Control (AVC)



Wire Feed



Rotation/Travel Control



Hot Wire Voltage Control



Oscillation

OPTIONAL FUNCTIONS





Motorized Wire Manipulator



Camera Illumination


MODEL

MODEL 415 PROGRAMMABLE MULTI-FUNCTION WELD POWER SUPPLY


STANDARD SOFTWARE



- Single or multipass welding schedule programming
- Up to 100 levels in one pass and up to 100 individual passes
- Pulsed current, travel, wire feed, oscillation, and wire manipulator synchronization
- Stepped or spiral travel programming
- Level programming in time or distance
- Data acquisition output
- Pre-programmed library of weld head definitions to reduce calibration and setup times
- User-modifiable programming field descriptions
- Multi-level password protection
- Project data recording
- Bar graph presentation of real-time welding parameters
- Foreign language software versions
- 2 User programmable fault I/Os



One Level Edit Screen




Start Up Screen

OPTIONAL SOFTWARE

Remote operation and offline programming via a network

SENSORS & FAULT MONITORS

- Torch Gas Flow Sensor an analog flow sensor that monitors gas flow rate (CFH)
- Coolant Flow Sensors monitor coolant flow rate and create a Sequence Stop if below 0.2 GPM
- Coolant Level Sensor senses coolant level in reservoir and displays to the operator if the level is low
- Over Temperature Sensors located in critical assemblies, will create ALL STOP conditions if certain assemblies get too hot
- Ground Fault prevents Sequence Start or creates an ALL STOP condition if the work piece ground is not connected



System Status Screen

MODEL 415 Programmable multi-function weld power supply

WHAT'S INCLUDED



M415 Package

- 1. M415 remote pendant with 15 ft. cable (4,5m)
- 2. Pendant cable extension 50 ft. (15m)
- 3. Ground cable with 400A ground clamp 50 ft. (15m) 8.
- 4. Weld head control cable 40 ft. (12m)
- 5. Weld head services cable 40 ft. (12m)

- 6. 10 ft. shielding gas hose
- 7. Input power cable, 25 ft. (7,6m)
- 8. Keyboard
- 9. Heavy-duty, reusable shipping crate
- 10. Software package and operator manual

COMPLEMENTARY PRODUCTS



Remote Vision System



Chart Recorder




Remote PC

WELD HEADS



Model 2



Model 43



Model 52 Heavy-Duty Pipe Weld Head

Leaders & Innovators in

Automated Orbital Welding

For further information please visit our website or contact us at 1-818-896-9556











www.arcmachines.com sales@arcmachines.com

HEADQUARTERSArc Machines, Inc.

10500 Orbital Way Pacoima, CA 91331 U.S.A. Tel: +1 / 818 / 896 / 9556 Fax: +1 / 818 / 890 / 3724 sales@arcmachines.com

EUROPEAN BRANCH OFFICE

Arc Machines, Inc.

Chemin du Lavasson 2, CH-1196 Gland, Switzerland Tel: +41 / 22 / 995 / 0051 Fax: +41 / 22 / 995 / 0059 sales@arcmachines.ch

GERMAN OFFICE

Arc Machines GmbH

Markelsbach 2 D-53804 Much, Germany Tel: +49 / 2245 / 91680 Fax: +49 / 2245 / 916868 sales@arcmachines.de

UK OFFICE

Arc Machines UK Limited Unit 2 Lamport Court Heartlands Business Park Daventry, NN11 8UF, UK Tel: +44 / 1327 / 312787 Fax: +44 / 1327 / 315034 sales@arcmachines.co.uk

MKT 415 PS / December, 2012 / E