

Oil Cooled Series

	Bantam	WT225	WT300	ACV360	ACV460	DRT300	DRT350	DRT850
Input volts	230/380/415	230/380/415	230/380/415	380/400/415	380/400/415	380/400/415	380/400/415	415
KVA rating	9.0	11.25	15.0	28.8	36.8	32.0	38.5	64.0
230V fuse	30A	40A	60A	-	-	-	-	-
415V fuse	20A	25A	35A	70A	85A	75A	90A	150A
Welding current range 50V	25-180	25-225	35-300	-	-	2x30-300	2x30-350	-
Welding current range 80V	30-130	40-135	50-220	35-360	30-460	2x30-220	2x50-250	2x30-420
Welding current range 100V	-	-	-	50-300	45-375	-	-	-
No. of welding current sections	20	72	72	104	104	144	144	144
Weight	75kg	137kg	165kg	303kg	352kg	386kg	432kg	705kg
Wheels	No	Yes	Yes	Yes	Yes	Yes	Yes	No
Oil capacity	22L	57L	57L	106L	158L	158L	158L	210L
Dimensions (mm)	370W 325D 390H	510W 470D 605H	510W 470D 605H	790W 560D 660H	970W 610D 660H	970W 610D 660H	970W 610D 660H	860W 860D 800H

	RT110	RT140	RT180	RT250	RT300	RT350	RT450	RT600
Input volts	200/220/240	230/380/415	230/380/415	230/380/415	230/380/415	380/400/415	380/400/415	380/400/415
KVA rating	5.5	7.0	9.0	12.5	15.0	17.5	25.5	34.0
230V fuse	15A	25A	30A	45A	60A	-	-	-
415V fuse	-	15A	20A	30A	35A	40A	60A	80A
Welding current range 50V	20-110	25-140	20-180	25-250	35-300	30-350	20-450	25-600
Welding current range 80V	25-75	30-95	30-130	45-185	50-220	50-250	45-325	50-410
Welding current range 100V	-	-	-	-	-	-	-	-
No. of welding current sections	16	20	72	72	72	72	144	144
Weight	60kg	68kg	137kg	166kg	195kg	211kg	260kg	350kg
Wheels	No	No	Yes	Yes	Yes	Yes	Yes	Yes
Oil capacity	22L	22L	57L	57L	74L	74L	106L	158L
Dimensions (mm)	370W 325D 390H	370W 325D 390H	510W 470D 605H	510W 470D 605H	615W 500D 660H	615W 500D 660H	790W 560D 660H	970W 610D 660H