Double Jackscrew clamps for aligning & reforming pipes

All clamps include:

Chain Clamps

- Length of chain required for the pipe range
- Double jackscrew jackbars listed for the pipe range
- Main block
- Fine adjustment
- Fitting alignment device
- Jackscrew wrench
- Parts and operating manual
- Metal Storage box
- Hi-Lo gauge



Features and advantages:

- Alignment can align all pipe schedules accurately.
- Reforming jackscrews enable the elimination of 'Hi-Lo' points either side of the weld joint. Can reform up to schedule 40 pipes.
- Adaptable one chain clamp covers the range of 8 cage clamps.
- No Tack Jackbars joints can be fully welded without removing the clamp.
- Versatile elbows, tees and other fittings can be accurately aligned using the Fitting Alignment Device.
- Quality jackbars are cast from high quality steel alloys.
- Additional jackbars can be added if extra pressure is required.
- Jackscrews Jackbars have two jackscrews with independently pivoting pads to compensate for uneven surfaces.
- Stainless Steel available in both carbon and stainless steel versions.

Part No.	Pipe Diameter Range "/mm	No. Of Jackbars	Reforms Pipe to Schedule	Aligns Pipe to Schedule	Shipping WT KGS
SCC12	1-12	4	40	80	12
SCC12SS	1-12	4	40	80	12
SCC20	4-20	7	40	80	33
SCC20SS	4-20	7	40	80	33
SCC36	10-36	8	40	80	67
SCC36SS	10-36	8	40	80	67
SCC54	10-54	13	40	80	82
SCC54SS	10-54	13	40	80	82

GBC Chain Clamps must not be used as a lifting device. Fittings must be independently supported at all times.